




Client Date Qty
 Project Type PO#

LS-STRIP-24V

Flexible LED Strip



Description

- CRI 80+(B CHIP) or CRI 90+ (BRIDGELUX CHIP)
- SMD 2835
- Made in Canada
- 50 000hrs + lifetime
- 5 years warranty
- 3-Step MacAdam's ellipse, single binning
- Reverse connexion protection
- IP20 or IP67

Specifications CRI 80+

Model	Protection	Power	Color Temperature	Lumens	LED/FT	Voltage	Beam angle	Maximum length	Width
LS-STRIP-24V-300LM-80-2,7K	IP20/IP67	4W/ft	2700K	300lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-300LM-80-3K	IP20/IP67	4W/ft	3000K	300lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-300LM-80-3,5K	IP20/IP67	4W/ft	3500K	300lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-300LM-80-4K	IP20/IP67	4W/ft	4000K	300lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-300LM-80-5K	IP20/IP67	4W/ft	5000K	300lm/ft	38pcs/ft	24V	120°	32 ft	10mm

Model	Protection	Power	Color temperature	Lumens	LED/FT	Voltage	Beam angle	Maximum length	Width
LS-STRIP-24V-600LM-80-2,7K	IP20/IP67	6W/ft	2700K	600lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-600LM-80-3K	IP20/IP67	6W/ft	3000K	600lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-600LM-80-3,5K	IP20/IP67	6W/ft	3500K	600lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-600LM-80-4K	IP20/IP67	6W/ft	4000K	600lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-600LM-80-5K	IP20/IP67	6W/ft	5000K	600lm/ft	38pcs/ft	24V	120°	32 ft	10mm

Model	Protection	Power	Color temperature	Lumens	LED/FT	Voltage	Beam angle	Maximum length	Width
LS-STRIP-24V-800LM-80-2,7K	IP20/IP67	8W/ft	2700K	800lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-800LM-80-3K	IP20/IP67	8W/ft	3000K	800lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-800LM-80-3,5K	IP20/IP67	8W/ft	3500K	800lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-800LM-80-4K	IP20/IP67	8W/ft	4000K	800lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-800LM-80-5K	IP20/IP67	8W/ft	5000K	800lm/ft	38pcs/ft	24V	120°	32 ft	10mm

Model	Protection	Power	Color temperature	Lumens	LED/FT	Voltage	Beam angle	Maximum length	Width
LS-STRIP-24V-1000LM-80-2,7K	IP20/IP67	10W/ft	2700K	1000lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-1000LM-80-3K	IP20/IP67	10W/ft	3000K	1000lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-1000LM-80-3,5K	IP20/IP67	10W/ft	3500K	1000lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-1000LM-80-4K	IP20/IP67	10W/ft	4000K	1000lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-1000LM-80-5K	IP20/IP67	10W/ft	5000K	1000lm/ft	38pcs/ft	24V	120°	32 ft	10mm



Client Date Qty
 Project Type PO#

LS-STRIP-24V

Flexible LED Strip

Specifications CRI 90+

Model	Protection	Power	Color temperature	Lumens	LED/FT	Voltage	Beam angle	Maximum length	Width
LS-STRIP-24V-300LM-90-2,7K	IP20/IP67	4W/ft	2700K	300lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-300LM-90-3K	IP20/IP67	4W/ft	3000K	300lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-300LM-90-3,5K	IP20/IP67	4W/ft	3500K	300lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-300LM-90-4K	IP20/IP67	4W/ft	4000K	300lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-300LM-90-5K	IP20/IP67	4W/ft	5000K	300lm/ft	38pcs/ft	24V	120°	32 ft	10mm

Model	Protection	Power	Color temperature	Lumens	LED/FT	Voltage	Beam angle	Maximum length	Width
LS-STRIP-24V-600LM-90-2,7K	IP20/IP67	6W/ft	2700K	600lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-600LM-90-3K	IP20/IP67	6W/ft	3000K	600lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-600LM-90-3,5K	IP20/IP67	6W/ft	3500K	600lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-600LM-90-4K	IP20/IP67	6W/ft	4000K	600lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-600LM-90-5K	IP20/IP67	6W/ft	5000K	600lm/ft	38pcs/ft	24V	120°	32 ft	10mm

Model	Protection	Power	Color temperature	Lumens	LED/FT	Voltage	Beam angle	Maximum length	Width
LS-STRIP-24V-800LM-90-2,7K	IP20/IP67	8W/ft	2700K	800lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-800LM-90-3K	IP20/IP67	8W/ft	3000K	800lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-800LM-90-3,5K	IP20/IP67	8W/ft	3500K	800lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-800LM-90-4K	IP20/IP67	8W/ft	4000K	800lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-800LM-90-5K	IP20/IP67	8W/ft	5000K	800lm/ft	38pcs/ft	24V	120°	32 ft	10mm

Model	Protection	Power	Color temperature	Lumens	LED/FT	Voltage	Beam angle	Maximum length	Width
LS-STRIP-24V-1000LM-90-2,7K	IP20/IP67	10W/ft	2700K	1000lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-1000LM-90-3K	IP20/IP67	10W/ft	3000K	1000lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-1000LM-90-3,5K	IP20/IP67	10W/ft	3500K	1000lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-1000LM-90-4K	IP20/IP67	10W/ft	4000K	1000lm/ft	38pcs/ft	24V	120°	32 ft	10mm
LS-STRIP-24V-1000LM-90-5K	IP20/IP67	10W/ft	5000K	1000lm/ft	38pcs/ft	24V	120°	32 ft	10mm

Dimensions

